




Wear parts

ABIMIG® A T 305 / 355 LW

ABIMIG® A T 405 LW





Gas nozzle (5 pcs.)	Ø A	X		Ø A	X	
Cylindrical	Ø 21	71 mm	145.D024	Ø 21	71 mm	145.D024
Conical	Ø 18	72 mm	145.D021**	Ø 18	72 mm	145.D021***
Tapered	Ø 16	69 mm	145.D022	Ø 16	69 mm	145.D022



Contact tip (10 pcs.)		M8	M8
E-Cu	Ø 0.8	140.0114	140.0114
	Ø 1.0	140.0313	140.0313
	Ø 1.2	140.0442	140.0442
	Ø 1.6	140.0587	140.0587
CuCrZr	Ø 0.8	140.0117	-
	Ø 1.0	140.0316	140.0316
	Ø 1.2	140.0445**	140.0445
	Ø 1.6	140.0590	140.0590***

For more contact tips see chapter "Accessories & special equipment"



Contact tip holder (5 pcs.)		
M8	014.D745.5**	014.D745.5***



Adapter piece (5 pcs.)		
	767.D668.5**	015.D080.5***



Torch neck liner for T-torches			
Standard	Ø 0.8	122.D037 (5 pcs.)	-
	Ø 1.0-1.2	122.D038** (5 pcs.)	122.D077 (5 pcs.)
	Ø 1.6	122.D045 (5 pcs.)	122.D078*** (5 pcs.)
Brass for Al	Ø 1.0	122.D040	122.D040
	Ø 1.0-1.2	122.D041	122.D041



Liner	Ø	305/355 for 3 m	305/355 for 4 m	305/355 for 5 m	405 for 3 m	405 for 4 m	405 for 5 m
Insulated liner	Ø 0.8	124.0011	124.0012	124.0015	-	-	-
	Ø 1.0	124.0026	124.0031	124.0035	124.D113	124.D114	124.D115
	Ø 1.2	124.0026**	124.0031**	124.0035**	124.D116***	124.D117***	124.D118***
	Ø 1.6	124.0041	124.0042	124.0044	124.D119	124.D120	124.D121

For more liner see chapter "Accessories & special equipment"

Standard equipment

* Included in the standard equipment for complete torches ABIMIG® A T 305 LW

** Included in the standard equipment for complete torches ABIMIG® A T 355 LW

*** Included in the standard equipment for complete torches ABIMIG® A T 405 LW